

CIMPERIAL® 35-880

High Performance Metalworking Fluid



APPLICATION:

CIMPERIAL® 35-880 is a multi-purpose, moderate to heavy-duty fluid for machining and grinding. It offers high performance in applications such as turning, drilling, milling, reaming, boring, tapping, broaching, sawing, and grinding applications. Good on most metals other than magnesium alloys.

FEATURES & BENEFITS:

- For most metals and all operations
- For use in a wide range of water qualities
- Good foam control in soft water and high-pressure applications
- Does not contain chlorine, boron or triazine
- Machines stay clean and parts are easy to wash

RECOMMENDED STARTING DILUTIONS:

CIMPERIAL® 35-880 is to be mixed with water for use. Always add concentrate to water. Add no materials to the concentrate or mix unless approved by CIMCOOL® Technical Service.

- Machining and Grinding: 5% to 10%
- The refractometer factor is 1.0
- 5% Mix pH is typically 8.7

SAFETY DATA SHEET:

Available at www.cimcool.ca

For additional information refer to its SDS, website or contact CIMCOOL® Technical Services at 1-888-254-1919.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

CIMCOOL FLUID TECHNOLOGY
3000 DISNEY STREET
CINCINNATI, OH 45209
8/2020 PC B02610